



**AN HSIN ENTERPRISE CO.,LTD**

NO. 100, ALLEY 5, LANE 123, SHE PI RD.,  
SHE PI LI, FENG YUAN CITY, TAICHUNG HSIEN,  
TAIWAN, R.O.C.

Email:anhsin@ms10.hinet.net Http://www.anhsin.com.tw  
TEL:04-25322384 FAX:04-25328828



# **AIR-COOLER**

## **FOG-MAKER**

*hydrodynamic force*

**AN HSIN ENTERPRISE CO.,LTD**

# Fog-Maker & Air-Cooler





## High Pressure Fog Maker

### FOG-MAKER & AIR-COOLER

- Standard High Pressure Fogging Machine



● Filter



● Electric Control Box



● High Pressure Electromagnetic Valve

## FEATURE

- One piece formed structure, easy to move, easy to assemble
- Proprietary patented connector, easy to dismantle, will never drip water.
- Proprietary high performance pump, high efficiency
- May be installed at any buildings, work with all types special connectors.
- Have timed control valve, may set up operation time at will.
- Simple structure, convenient to maintain.
- Build in electric box, does not need additional electric box.
- Stainless steel material, sturdy and beauty.

- Economic High Pressure Fogging Machine



● Filter

MODEL	NM-FOG
DIMENSIONS L/W/Hmm	Economic 380X290X320 Standard 600X380X567
PUMP TYPE	2 PISTON
PRESSURE	60kg/cm <sup>2</sup>
DISCHARGE VOLUME l/min	4 l/min
HP	0.5 HP
VOLTAGE/Hz	110V/220V/60Hz
TIMER	RUNNING TIME
	3sec-30min
STOPPING TIME	3sec-30min
NET WEIGHT kgs	30 kg 56 kg

● Golf Course



● High-Temperature Casting



● Orchid Cultivation Field



● Orchid Marketplace



**NEW**  
**PATENT COMMODITY**



## Mobile Fogging Fan

### Specification :

- Voltage : 110V ~ 220V
- Working pressure : 70kg/cm<sup>2</sup> (1000PSI)
- Motor: 1/10HP
- Nozzle Q'ty : 0.1MM nozzle \*3
- Max spray volume : 500 CC/min
- Safety protection device : low-water power supply cut-off switch
- Volume : 70CM\*40CM\*32CM
- The size of the water tank : 32CM\*32CM\*29CM
- Volume of the water tank : 29L
- Weight of the fan : 7.38KG
- Weight amount : 42.2KG
- Control : Automatically controlled system

### Function :

- Can control manually and automatically.
- Adjustable time controls.

Blow in the distance : 20M  
Blowing angle : adjustable



NAME : High Pressure Spray Deceleration Pad

PAT.NO.M313549

### Function Description :

Decompression spray pad not only has the function of deceleration (deceleration can bear 35 tons of high-pressure and safety reflecting board), but also has function of making fog by using top-down approach. It can eliminate the heat on ground because the sun generates heat during the daytime. The traditional fog pipe needs to overhead or dig the pipeline when the pipes need to be got through the passage or vehicle road. It is inconvenience to install. However, our products only need four ground nails to install, which is easier and convenience.



Reduced Temperature/Maintains the humidity  
Manufacture Mist/Disinfection



Application scope: car park, central reservation,